

EXCAVATOR MULCHERS

PMM/HY



from 25 to 45 HP



Ø4 cm max



from 3,5 to 5,5 t

MULCHER WITH HAMMER/FLAIL ROTOR FOR EXCAVATORS.

Thanks to its compact dimensions and versatility, the PMM/HY is the most requested model for grass and brush mulching in FAE's small mulcher lineup. The mulcher can be equipped with a standard 16cc motor or an optional 27cc motor for mounting on 3.5 to 5.5 ton excavators. The flow control valve ensures an easy and rapid mounting of the mulcher without adjustments or modifications to the hydraulic system of the excavator.




STANDARD EQUIPMENT

Anti dust machine body
Belt transmission
16cc gear motor with integrated anticavitation valve
Hydraulic hoses
Flow control system valve (only with 16 cc and 27 cc motors)
Welded counter blade
Rear roller
Self levelling protection rubber
Possibility to have the rotor equipped with PML hammers or Y-flails

OPTIONS

27cc gear motor with integrated anticavitation valve
17/34cc variable manual displacement hydraulic piston motor with relief and anticavitation valve
Customized attachment bracket with pins
Attachment plate with self levelling device
Different teeth



Hydraulic hoses

Various types of hydraulic motors

to adapt to different models of excavators

Steel counter-blades

helps mulch material into a smaller final size

Flow control system valve

to protect the motor from excessive flow

Anti dust machine body

Self-cleaning support roller

MODEL	Power (HP)		Flow rate (L/min)		Pressure (bar)		Excavator weight (t.)		Working width (mm)	Weight (kg)	Max shredding diameter (mm)	No. teeth	
	min	max	min	max	min	max	min	max				PML	Y
PMM/HY 100	25	45	35	75	150	210	3,5	5,5	1015	240	40	16	16
PMM/HY 125	30	45	35	75	150	210	4,0	5,5	1255	265	40	20	20
PMM/HY 150	35	45	35	75	150	210	4,5	5,5	1495	290	40	24	24

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.